

	Alloy	6063T6
	Finish	Bright Anodised AA5
		Satin Silver Anodised AA5
<b>Dimensions</b>	Width	88mm
	Depth	20mm
	Length	2000mm (standard base)
	Weight	1.327 kg/mt (2 part total)
<b>Activation Insert</b>	Materials:	Flexible PVC-DVF406
	Dimensions (external)	Standard length rolls - 5, 10, 15mt
	Max Width	54mm
	Max depth	9mm
	Active impact zone	34mm
	Weight/mt (inc Copper)	0.353kg/mt
	Colours	Red- 033HMF/25K-200. Green -GN590HMF/25K-200. Blue -BE047HMF/25K-200.
	Elongation @ break (%)	380
	Shore A15 Hardness	63
	UV stabilised	yes
	Cold Flex Temp	-28 c
	Tensile (Mpa)	14
	I.P. Rating	IP65
<b>Contact Conductor</b>	Material	ED Copper
	Width	10mm
	Quality	CTS790
	Treatments	Zinc-Chromate Passivated
<b>LED Light Strip</b>	Dimensions	8mm x 2.5mm
	LEDs/mt	30
	Colour	Bright White
	Operating Temperature	-25c to +60c
	Voltage	DC 12v
	LED Life	50,000 hours
	Power consumption	<a href="#">180mA/metre@12V (see note1)</a>
<b>LED Controller</b>	Supply Voltage	12V DC
	Supply Current	80mA + LED current (see note 1)
<b>End Caps</b>	Construction	2 part - self locking
	Material	ABS
	Weight (set)	42 grams



<b>Optional Extras</b>		
<b>Finishes</b>	Any coloured anodised finish to special order	Minimum order applies
<b>Anti-Microbial Protection</b>	Product	Hygienilac
	Standards	BS6250 sever usage
	Approvals	FDA, HSE, EPA, NHS

*Note 1: LED Current dependent on control setting choice - Max 180mA/metre full brightness.*

*Current is reduced by changing choice of light mode*

**For more information call our sales team on 01943 876600**

**or email: [sales@cronapress.co.uk](mailto:sales@cronapress.co.uk)**

